



## Mobil 1™ FS X2 5W-40

[www.actlubricants.eu](http://www.actlubricants.eu)

Mobil Passenger Vehicle Lube , United States

Advanced Full Synthetic Motor Oil

### Product Description

Mobil 1™ FS x2 5W-40 European Car Formula is an advanced full synthetic motor oil engineered for the latest gasoline and diesel (without DPFs) engine technology delivering excellent all-around performance. It provides exceptional cleaning power, wear protection and overall performance. Mobil 1 FS x2 5W-40 keeps your engine running like new and protects for 10,000 miles\*

\*Protects for up to 10,000 miles or 1 year, whichever comes first. To learn more about the Mobil 1 Limited Warranty, visit us at Mobil.US.

### Features and Benefits

Mobil 1 FS x2 5W-40 is made with a proprietary blend of ultra-high performance synthetic basestocks fortified with a precisely balanced component system. Key features and potential benefits include:

Features	Advantages and Potential Benefits
Outstanding thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Excellent low temperature capabilities	Outstanding cold starting and fast lubrication to protect against wear
Active cleaning agents	Designed to clean up sludge left behind in your engine
Low oil volatility	Helps reduce oil consumption
High viscosity index	Excellent overall lubrication and wear protection performance for many driving styles and conditions, from mild to severe

### Applications

Mobil 1 FS x2 5W-40 is recommended by ExxonMobil for all types of vehicles, including high-performance turbo-charged, supercharged gasoline and certain diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

- Mobil 1 FS x2 5W-40 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

### Specifications and Approvals

This product has the following approvals:
MB-Approval 229.3
Porsche A40

**This product has the following approvals:**

VW 502 00

VW 505 00

**This product is recommended for use in applications requiring:**

API CF

**This product meets or exceeds the requirements of:**

ACEA A3/B3

ACEA A3/B4

API SJ

API SL

API SM

API SN

**Properties and Specifications**

Property	
Grade	SAE 5W-40
Flash Point, Cleveland Open Cup, °C, ASTM D92	227
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	80
Density @ 15 C, g/cm <sup>3</sup> , ASTM D4052	0.849
Pour Point, °C, ASTM D97	-45
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.6

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

**Exxon Mobil Corporation**

22777 Springwoods Village Parkway

Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product

performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved