

Klübersynth AG 14-61

Light-coloured special lubricant for open drives



Your benefits at a glance

- Good pumpability and metering via centralised lubrication systems also at low temperatures
- High corrosion protection also when exposed to salt water
- Longer service life of girth gear/pinion drives due to good wear protection characteristics even under vibration conditions
- No contamination of machine environment due to use of white solid lubricants
- Low consumption due to excellent adhesion even at low temperatures

Your requirements - our solution

Klübersynth AG 14-61 has been especially designed for girth gear/pinion drives and plain bearings in wind turbines. The lubricant is resistant to high loads and provides very good corrosion protection properties. It can be used in a wide service temperature range and is therefore pumpable at temperatures as low as minus 30 °C. The grease offers good pressure and wear resistance and is free from inorganic solid lubricants like MoS₂ and graphite. Due to its good compatibility with commercial sealing materials Klübersynth AG 14-61 is suitable for wide ranging applications.

Application

Klübersynth AG 14-61 has been designed for girth gear/pinion drives and plain bearings in wind turbines. The lubricant is also suitable for

low-speed rolling bearings, plain bearings, sliding and guide rails.

Application notes

Klübersynth AG 14-61 can be applied by means of brush, spatula, grease gun, grease metering gun, automatic low-quantity or standard metering systems, grease cartridge, and centralised lubrication systems. We recommend conducting a metering test in the original dosing device under practical operating conditions.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klübersynth AG 14-61
Cartridge 450 g	+
Can 1 kg	+
Bucket 5 kg	+
Bucket 25 kg	+
Drum 200 kg	+

Characteristics	Klübersynth AG 14-61
Article number	017184
Composition	solid lubricant
Composition, thickener	aluminium complex soap
Composition, type of oil	synthetic hydrocarbon oil

Klübersynth AG 14-61

Light-coloured special lubricant for open drives



Characteristics	Klübersynth AG 14-61
Solid lubricants	approx. 20 % by weight
Colour space	white
Texture	homogeneous
Service temperature, lower limit	-50 °C
Service temperature, upper limit	120 °C
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, lower limit	330 0.1 mm
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, upper limit	360 0.1 mm
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 53000-1, based on standard / ASTM D445 / ASTM D7042, 40°C	approx. 65 mm ² /s
Flow pressure, DIN 51805-2, -50°C	≤ 1400 mbar
Dropping point, DIN ISO 22286 / IP 396	≥ 170 °C
FZG scuffing test, DIN ISO 14635-3, based on standard, A / 2.8 / room temperature, failure load stage	≥ 12
Water resistance, DIN 51807-1, 3 h, 90°C	0 - 90 rating
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 95 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.